

Industrial Remote Touch Display Solutions

Industrial Remote Display Host

Model: A203CG



Features

- Supports Remote Display Function
- Easy-To-Install: RJ-45 Cable x 1
- Easy-To-Deploy: TCP/IP Protocol Support
- Desktop/ VESA Mount



Specifications

System	
Front I/O	Mini-USB x 1, Line-out x 1, DVI/VGA input x 1, RJ-45 x 1, LED x 2, Button (SW18SW2) x 2
Rear I/O	DIP Switch
Side I/O	—
OS support	Windows® XP, Windows® 7
Mechanical	
Construction	Steel front bezel & chassis
Mounting	Wall/ Desktop/ VESA 75/100
Dimension	—
Carton Dimension	—
Gross Weight	—
Net Weight	—
Environmental	
Operating Temperature	32°F ~ 122°F (0°C ~ 50°C)
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Storage Humidity	10%-95% @ 40°C; non-condensing
Vibration	1 g rms/ 5-500Hz/ Random operation
Shock	15 G peak acceleration (11 msec. Duration)
EMC	CE/FCC Class A
Power Supply	
DC Input	12V DC w/ power adapter

- Note: Users have to select the Remote Display to work with the A203CG