



## DCM1200 Series



### Key Features

- Support for Windows® XP Embedded or Windows® XP Professional
- Integrates major thin-client/ server computing protocols (Citrix ICA, Microsoft RDP), terminal emulation suite; and web browsers
- Comprehensive and intuitive remote device administration through server-based iTechLCD Device Manager software
- Configurable for thin-client/ server computing, browser-based computing, or local application shell
- Comprehensive set of USB and full legacy I/O ports for peripherals and accessories
- VESA-mountable for flexibility in mounting and deployment (75mm)
- Options for IR touch screen
- Optional integrated 802.11 a/b/g wireless LAN adapter

The DCM1200 digital terminal integrates a vivid display with flexible computing in one slim, mountable design. The DCM1200 features the integration of a bright 12" LCD display, over an efficient and powerful x86 1.5GHz-powered thin client platform, with options for IR touch screen and internal wireless communication. The full-featured yet elegant, space-saving package accommodates a range of accessories and peripherals to support a wide variety of vertical applications.

### Standard Package

1. 1 DCM1200
2. AC/DC adapter with power cord
3. Documentation

### Major Options

- Built-in 802.11a/b/g WLAN
- IR touch screen

## Optional Accessories

- **Keyboard Tray (1)**

The USB keyboard tray and matching keyboard form perfect complement to the DCM1200/ 1500/ 1700/ 2200 with easy-to-attach bracket, and protective keyboard holder. Keyboard (Mini-USB Keyboard w/ Hub or Waterproof Keyboard) is not included.

- **Mini-USB Keyboard w/ Hub (2)**

88-key USB keyboard in compact form factor connects directly to the device. USA Only.

- **Waterproof Keyboard (3)**

Wipeable for easy cleaning; dimmable backlighting; advanced laser process for durable legends; 88 keys; compact size.

- **Optical USB Mouse (4)**

For comfort and control of your computing experience, this two-button mouse has fast, accurate response.

- **Full Size USB Keyboard (5)**

This keyboard has a USB connector, 107-key enhanced Windows layout, membrane tactile switch, 3 hot keys, and is spill-proof.

- **AC Adapter with Power Cord (6)**

For DCM1200/ 1500/ 1700/ 2200

- **Display Base Stand (7)**

1.Stable, hinged stand with 115 to 160 degree tilt of the display  
2.Locking mechanism for touch screen applications and VESA-compliant mounting



## Specifications

<b>System</b>	<b>Display</b>	12" TFT LCD; 50,000 hours lamp life
	<b>Display Resolution</b>	1024 x 768
	<b>Processor</b>	1.5 GHz x86
	<b>RAM</b>	1GB
	<b>Storage</b>	2GB, 4GB, 8GB or 16GB flash module; 2.5" HDD
	<b>Operation System</b>	Microsoft® Windows® XP Embedded or Windows® XP Professional
	<b>Network Interface</b>	Ethernet 10/100 MB Base-T LAN; 802.11b/g or 802.11a/b/g WLAN
	<b>I/O Ports</b>	1 Serial port, 2 USB 2.0 ports, RJ45 connector for Ethernet, 1 Audio-out jack, 1 Microphone-in jack, 1 Line-in jack, and 1 DC-in jack
	<b>Speaker</b>	Built-in speaker
<b>Power</b>	<b>AC/ DC Adapter</b>	<b>Input:</b> 100 – 240V AC; <b>Output:</b> 18.5V DC, 3.5A
<b>Mechanical</b>	<b>Enclosure</b>	ABS + PC Plastic
	<b>Dimensions (H x W x D)</b>	9.09 x 12.1x 2.51 in; 231 x 309 x 64 mm
	<b>Weight</b>	8.8 lbs (4Kg)
	<b>Power Cords</b>	North America, EU, UK and China
<b>Environmental</b>	<b>Water and Dust Resistance</b>	IP65 sealed front IR Touch panel. (Not applicable for non-IR sku)
	<b>Regulatory</b>	FCC Class B, CE, UL, RoHS compliant
	<b>Operating Temperature</b>	0° – 40°C
	<b>Humidity</b>	0% – 90% non-condensing