

# Features Highlight:

- High-Brightness LCD Panel
- Work under Direct Sunlight\*\*
- All Weather Proof IP65/NEMA4 Enclosures
- Operating Temperature -40C To 50C\*\*
- Integrated Heater and Air conditioner

- Vandal Resistant AR Glass & housing
- Unique Front Access Design for Easy Service
- Unique Quick Glass remove Design for Easy Service
- Build-in Monitoring Via RS232
- Optional Embedded PC or Media Player
- Optional Video Via CAT5 Extenders

# **Specifications:**

Display size (Diagonal) 64.5 inch

Brightness 1500nits (Typ)

Active area 1428.48 (H) x 803.52 (V)

Pixel pitch 0.744

 Display Colors
 1073.4M (10-bit)

 Resolution
 1920 x 1080

 Viewing angle
 89/89/89/89

 Contrast Ratio
 4000 : 1 (Typ)

 Response Time
 6.5ms

 IP Class
 IP65/NEMA4

 Video inputs
 HDMI, VGA

Input voltage 110V(GS6500L1) or 220V (GS6500L2)

Operating temperature range -40F to + 122F (Over 100F Not Recommended facing

East/West Directly)\*\*

Front glass type Anti Resistive Laminated glass

Portrait version GS6500P. Please contact SuntronicLCD for details

Weight 550 lbs (Est.)

External dimensions (62.7" W x 37.7" H x 15"D) (1592mmW x 957mmH x 377mm D)

Warranty One Year Standard Return to Depot Warranty (Optional 2 yr extended Warranty

The information in this document is subject to change without notice



### **High Quality Parts**

Our company uses only the best, using only High Quality parts along with components in USA or imported from Korea, Taiwan and Germany, for quality that you can trust!



### **Customer Service**

Our customer service reps are here to help you with your Outdoor LCD sign. From general questions to technical support, we leave you feeling completely satisfied.



#### US Manufactured

Our Outdoor LCD Signs are assembled, tested and shipped from our very own factory, giving us the ability to customize signs to your











