Multi Touch LCD Monitors

32" Wide Multi Touch LCD Monitor
Model: OCHW3200MPCT

Features

- Using NEC Display Model V322
- Projected Capacitive Multi-Touch
- OPS Expansion Slot for Internal PC
- Internal 8W Speakers

Product Specifications:

Size/Type	32 inch Diagonal/ SPVA Panel Technology
Touch Technology	Projected Capacitive (up to 40 Touch Points with Win 7/8)
Resolution	1366 x 768
Brightness	450 cd/m2
Audio	Built-in, Low-profile 8W speakers x 2
Contents of Packaging	User's Manual, Power Cord, Wireless Remote, Batteries, Video Cable(s), Setup Sheet & Driver CD
Contrast Ratio	3000:1
Dimensions (W x H x D)	**Net (with stand):**
	31.0 x 20.3 x 9.4 in./786.8 x 516.5 x 240mm
	Net (without stand):
	31.0 x 18.7 x 3.7 in./786.8 x 476.2 x 93.5mm
Input Signal	Video: ANALOG RGB Vp-p / 75 Ohms
	Sync: Separate sync: TTL Level (Positive/Negative)
Input	HDMI, DVI-D, DisplayPort
	Analog 15-pin D-sub (VGA)
	5 BNC (RGB/HV, DVD/HD or Composite)
	BNC Composite
	S-Video
Limited Warranty	3 Years Parts and Labor Including Backlight
Operating Humidity	20-80%
Operating Temperature	5-40° C/41-104° F
Storage Humidity	10-90%
Storage Temperature	-20-60° C/-4-140° F
Pixels Per Inch	49
Power Consumption	(typical) On: 88W / Power Savings Mode: <1W
Synchronization Range	Horizontal: 31.5-91.1 KHz (Analog) / 31.5-91.1 KHz (Digital)
	Vertical: 50-85 Hz Analog / 50-85 Hz Digital
VESA Hole Configuration Spec.	200 x 200mm (4 hole)
Viewing Angle	178° Vert. 178° Hor. (89U/89D/89L/89R)@ CR>10
Weight	(with stand) 29.5 lbs./13.4 kg / (without stand) 26.7 lbs./12.1 kg
Additional Features	Ethernet Controllable, TileMatrix (5x5), TileComp, PIP/POP/Side by side picture, 6-axis color adjustment, 10-bit gamma, programmable zoom, scheduler, off-timer (countdown), screen saver, vacation switch, AutoBright, Windows Vista certified, portrait mode capable, color temperature adjust (2600-10k)