

Industrial Display

21.5" Industrial Display, 2 point PCT touch
Sophisticated Bezel-Free Design Smooth touch
surface across the entire face of the monitor for
refined aesthetics and easy cleanability.

Model: SW2150-TPC-D



SPECIFICATIONS

Panel Type	AUO 21.5-inch LCD Panel
Active Display Area (mm)	248.25 (H) x 248.25 (V)
Pixel Pitch (mm)	0.276 (H) x 0.276 (V)
Number of Pixels	1920(x 3) x 1080
Contrast Ratio	1000 : 1 (Typ)
Display Color	16.7M colors (6-bits + HiFRC)
USB HUB	1 Internal USB + 2 External USB
Touch Screen	2 Point PCT Touch
Brightness (cd/m^2)	250 cd/m^2
Backlight	LED Backlight unit
Viewing Angle (CR>=10)	-80 ~ +80 (H) ; -80 ~ +80 (V)
Synchronization	31.5 ~ 85 KHz / 60 ~ 80 Hz
Recommended Resolution	1920(x 3) x 1080 @ 60Hz
Signal Connector	15 pin D-Sub / DVI Cable
Power Source	DC 24V Input
Power Consumption	22 Watt Typical, Normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC1 / 2B
Temperature	0 to +50
Temperature Range Storage	-20 to +60
Dimensions (mm)	536.2 x 327.7 x 42.7 mm

DRAWINGS

