

Industrial Chassis/Wall Mount Metal Housing

Industrial Chassis/Wall Mount Metal Housing , 10" 4:3 LED 250nits,
1024x768,VGA Input, Side or Top OSD with SAW
(Surface Acoustic Wave) touch Screen and USB Controller



(Model: TCH1000-SW)



FEATURES:

- * VGA Input
- * Optional RCA Composite Video + Speaker
- * Optional 5-Wire Resistive / Capacitive / SAW Touch supports all Windows / Linux OS
- * 4:3 Screen LED Back-Light 250nits
- * Supports 75x75 VESA Mounting on the back-case

System Specifications

Panel	
Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel number	1024(H) x 768(V)
Pixel Pitch	0.198(H) x 0.198(V) mm
Display Size	10" viewable diagonal area
Active Area	202.8(H) x 152(V) mm
Color Depth	262K colors
Light Source	20,000 hrs (typ) LED BL
Brightness	250 cd/m ² (typ)
Contrast Ratio	500 : 1
Viewing Angle	horizontal(typ) (L ~ R : - 65o ~ +75o) vertical (typ) (U ~ D : - 50o ~ + 70o)
Input Signal	
Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh : 30 - 82Khz , Fv : 60 - 75Hz
Resolution	
Supported	1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz 640 x 480@60 / 70 / 75 Hz 720 x 400@60 / 70 Hz 640 x 350@ 70 Hz
Recommended	1024 x 768@60 Hz
Control	
Front Panel	Power Menu Select + (Inc) - (Dec) Auto Adjust Brightness Contrast H-Position V-Position
Winsticker (OSD)	Phase Color Default Volume Language Memory Recall
Power	
Input Voltage	AC: 90 to 260VAC, 50 / 60 Hz DC:12V/ 1.2A
Power Rating	
Operation	10 watt
Off	< 1 watt
Audio	2W x 1 Speaker
Operating Condition	
Temperature	-20°C ~ 70°C
Humidity	10% ~ 90% (no condensation)
Storage Condition	
Temperature	- 30°C ~ 80°C
Humidity	10% ~ 90% (no condensation)
Dimensions	
Physical	(W x H x D)
Weight	
N.W. / G.W.	
Options	
Video-In	2x RCA-Connect
Touch Screen	5-wires Resistive type USB Interface
Certification	FCC, CE