

OPEN FRAME LCD MONITOR

Open frame LCD Rear OSD with Rear Housing, 10.4" 4:3 CCFL
350nits, 800x600,VGA Input,Side or Top OSD with SAW
(Surface Acoustic Wave) touch Screen and USB Controller



(Model: TOP1040-SW)

FEATURES:

- * VGA Input / Optional DVI Input
- * Optional RCA Composite Video + Speaker / Optional HDMI Input
- * Optional 5-Wire Resistive / Capacitive Touch supports all Windows / Linux OS
- * 4:3 Screen CCFL Back-Light 350nits

System Specifications

| | |
|----------------------------|--|
| Panel | |
| Cell Type | Color active matrix TFT (Thin-Film-Transistor) LCD panel |
| Pixel Arrangement | RGB vertical stripe |
| Glass Surface | Anti-Glare coating |
| Pixel number | 800(H) x 600(V) |
| Pixel Pitch | 0.264(H) x 0.264(V) mm |
| Display Size | 10.4" viewable diagonal area |
| Active Area | 211.2(H) x 158.4(V) mm |
| Color Depth | 262K colors |
| Light Source | Long life, 50,000 hrs (typ) |
| Brightness | 350 cd/m ² (typ) |
| Contrast Ratio | 300 : 1 |
| Viewing Angle | horizontal(typ) (L ~ R : - 50o ~ +50o) vertical (typ) (U ~ D : - 35o ~ + 35o) |
| Input Signal | |
| Video | Analog RGB (0.7/1.0 Vp-p, 75 ohms) |
| Sync | Composite Sync |
| Frequency | Fh : 30 - 82Khz , Fv : 60 - 75Hz |
| Resolution | |
| Supported | 1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz 640 x 480@60 / 70 / 75 Hz 720 x 400@60 / 70 Hz |
| Recommended | 800 x 600@60 Hz |
| Control | |
| Front Panel | Power Menu Select + (Inc) - (Dec) Auto Adjust Brightness Contrast H-Position V-Position |
| Winsticker (OSD) | Phase Color Default Volume Language Memory Recall |
| Power | |
| Input Voltage | AC: 90 to 260VAC, 50 / 60 Hz DC:12V/ 1.2A |
| Power Rating | |
| Operation | 25 watt |
| Off | < 5 watt |
| Audio | 2W x 1 Speaker |
| Operating Condition | |
| Temperature | -10 ~ 65 |
| Humidity | 10% ~ 90% (no condensation) |
| Storage Condition | |
| Temperature | -30 ~ 70 |
| Humidity | 10% ~ 90% (no condensation) |
| Dimensions | |
| Physical | (W x H x D) |
| Weight | |
| N.W / G.W | 3Kg /4Kg |
| Options | |
| Video-In | 1x RCA-Connector 1xS-Video |
| Touch Screen | USB,RS-232 Interface |
| Certification | FCC, CE |

Model: TOP1040



Drawings

