

Panel Mount Aluminum Front IP65

Panel Mount Aluminum Front IP65 Water Proof LCD Monitor,
10.4" 4:3 CCFL 350nits, 800x600, VGA Input, Side or Top OSD



(Model: TPM1040)

FEATURES:

- * Aluminum front panel meet IP65 standard
- * Analog VGA and DVI input interface support
- * Optional S-video and RCA
- * Optional support 9~36V DC power input for mobile application
- * USB or RS-232 interface touch screen
- * Anti-Glare Tampered glass
- * Optional 5-Wire Resistive Touch Sensor
- * RoHS Compliance
- * Support Wall/Rack/Arm/Panel/VESA 75 mount
- * Chassis Color Silver OR Black



System Specifications

Panel	
Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel number	800(H) x 600(V)
Pixel Pitch	0.264(H) x 0.264(V) mm
Display Size	10.4" viewable diagonal area
Active Area	211.2(H) x 158.4(V) mm
Color Depth	262K colors
Light Source	Long life, 50,000 hrs (typ)
Brightness	350 cd/m ² (typ)
Contrast Ratio	300 : 1
Viewing Angle	horizontal(typ) (L ~ R : - 50o ~ +50o) vertical (typ) (U ~ D : - 35o ~ + 35o)
Input Signal	
Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh : 30 - 82Khz , Fv : 60 - 75Hz
Resolution	
Supported	1024 x 768@60 / 70 / 75 Hz, 800 x 600@60 / 70 / 75 Hz, 640 x 480@60 / 70 / 75 Hz, 720 x 400@60 / 70 Hz, 640 x 350@ 70 Hz
Recommended	800 x 600@60 Hz
Control	
Front Panel	Power , Menu,Select , + (Inc) , - (Dec) , Auto Adjust, Brightness, Contrast, H-Position, V-Position
Winsticker (OSD)	Phase, Color, Default,Volume , Language, Memory Recall
Power	
Input Voltage	AC: 90 to 260VAC, 50 / 60 Hz DC:12V/3A
Power Rating	
Operation	25watt
Off	< 5 watt
Audio	2W x 1 Speaker
Operating Condition	
Temperature	-10C~65C
Humidity	10% ~ 90% (no condensation)
Storage Condition	
Temperature	-30C~70C
Humidity	10% ~ 90% (no condensation)
Dimensions	
Physical	264 x 2 25 x 40 .5 mm (W x H x D)
Weight	
N.W. / G.W.	Kg /Kg
Options	
Video-In	1x RCA-Connector 1xS-Video
Touch Screen	5-wires Resistive type, USBor RS-232 Interface
Certification	FCC, CE

Accessories

- * VGA Cable
- * DVI Cable
- * S-Video Cable
- * RCA Cable
- * Universal / Auto-Sensing, 90 to 260V AC
- * Touch Panel Driver CD
- * User Manual

Drawings

