

Panel Mount Aluminum Front IP65

Panel Mount Aluminum Front IP65 Water Proof LCD Monitor, 12.1"
Wide 16:9 CCFL 450nits, 1280x800,VGA Input, Side or Top OSD with
5 Wire Resistive Touch Screen and USB Controller

(Model: TPMW1210-TR)



FEATURES:

- * VGA Input / Optional DVI Input
- * Optional RCA Composite Video + Speaker
- * Optional 5-Wire Resistive Touch supports all Windows and Linux OS
- * 16:9 Wide Screen CCFL Back-Light 450nits
- * Support 75x75 VESA Mounting on the back-case



System Specifications

Panel	
Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel number	1280(H) x 800(V)
Pixel Pitch	0.204(H) x 0.204(V) mm
Display Size	12.1" wide viewable diagonal area
Active Area	216.12(H) x 163.2(V) mm
Color Depth	262K colors
Light Source	Long life, 50,000 hrs (typ)
Brightness	450 cd/m ² (typ) 4 CCFL
Contrast Ratio	300 : 1
Viewing Angle	horizontal(typ) (L ~ R : - 70o ~ +70o)
Input Signal	
Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh : 30 - 82Khz , Fv : 60 - 75Hz
Resolution	
Supported	1280 x 800@60 / 70 / 75 Hz
Recommended	1280 x 800@60 Hz
Control	
Front Panel	Power , Menu,Select , + (Inc) , - (Dec) , Auto Adjust, Brightness, Contrast, H-Position, V-Position
Winsticker (OSD)	Phase, Color, Default,Volume , Language, Memory Recall
Power	
Input Voltage	AC: 90 to 260VAC, 50 / 60 Hz DC:12V/ 1.2A
Power Rating	
Operation	30watt
Off	< 5 watt
Audio	2W x 1 Speaker
Operating Condition	
Temperature	-10 ~ 65
Humidity	10% ~ 90% (no condensation)
Storage Condition	
Temperature	- 30 ~ 70
Humidity	10% ~ 90% (no condensation)
Dimensions	
Physical	264 x 2 25 x 40 .5 mm (W x H x D)
Weight	
N.W. / G.W.	
Options	
Video-In	1x RCA-Connector 1xS-Video
Touch Screen	5-wires Resistive type, USBor RS-232 Interface
Certification	FCC, CE

Model: TPM1210



Drawings

