

Teleprompter High Brightness LCD Display

15" Teleprompter High Brightness LCD Display,
Reverses images internally with no special
equipment or software needed.
(Model: PCH1500HB)



Features:

- XGA 1024(H) x 768(V) resolution
- 12 CCFLs
- High contrast ratio: 500:1 (Typical)
- Ultrahigh brightness: typical 1500 nits, sunlight readable color TFT-LCD module
- Application: Industrial PC, KIOSK, POS system, Information terminal display, ATM, Medical...for the indoor or outdoors environment.
- Client can access lamp situation by RS232.

Specifications:

Active Area: 304.1mm(H) x 228.1mm(V) (15" diagonal)
Luminance: Up to 1500nits (Typical)
Bezel Opening Area: 307.4mm(H) x 231.3mm(V)
Outline Dimension: 326.5mm x 253.5mm x 38.4mm (Ref.)
Max. Resolution: 1024 (R,G,B x 3) x 768 pixel
Uniformity: 80% (Typical)
View Angle: +70°--70°(H), +60°--65°(V) (Typical)
Pixel Pitch: 0.297mm(H) x 0.297mm(W)
Electrical Interface: LVDS (1Ch)
Power Consumption: 44.4W (Typical)
Display Mode: TN Mode, Normally White
Support Colors: 16.2M colors (6-bit + FRC)
Inverter: TI811-12C

Mirror Image Features



**Reverses images internally - no special equipment
or software needed!!**

Weight: 1610g
Operating Temperature: 0~+50°C
Lamp Lifetime: 50,000 hours at 25 (IL:5mA)
HB Total thickness: 43.7mm

Model: Photo Gallery



Mechanical Drawings:

