



**23.8" Open Frame Monitor with 2500nits Brightness**  
 1920x1080 resolution, I/O:VGA/DVI/HDMI, power: 100~240V AC-in, metal chassis with rear VESA mount and ear mount design, built-in auto temperature and brightness control accessories: VGA cable x1, light sensor cable x1

**Model: GOPW2380HB2**

**FEATURES:**

- 23.8" LCD support full HD 1080P
- 2500 nits extreme high brightness
- Video signal IO: VGA / HDMI / DVI
- Special 24/7 long-term operation design
- Auto temperature/ brightness control
- Detachable ear mounting brackets design
- RS232 command control port

**SPECIFICATIONS:**

Function	Items	Description	Remark	
Display	Display area (mm)	527.04 (H) x 296.46 (V)	23.8" diagonal	
	Brightness (nits)	2500		
	Optimum resolution	1920 x 1080		
	Contrast Ratio	3000 :1		
	View angle	178 / 178 degree	In all direction	
	Backlight Life	50,000 hours		
System	Video input	VGA / HDMI / DVI		
	Video output	NA		
	Audio	Built-in	(Option)	2Wx2
		Extend	Line-out	
	Memory	NA		
	Storage	NA		
	Ethernet	NA		
	Wireless	NA		
Special Control	Manual	NA		
	OSD	5 keys at back side		
	RS232	YES		
	Display feedback	NA		
Power	Power Input voltage	AC 100-240 V		
	Consumption (W)	120 (typ.)		
Mechanical	Outline (mm)	545.60 x 324.51 x 53.0 (D)	The 4 brackets are not included (Reference to drawing)	
	Mounting	200 x 200/ 100 x100 (mm) VESA		
	Others	NA		
Environment	Operating temp.	<u>0~45 °C</u>	Auto temperature control	
	Storage temperature	<u>-10~55 °C</u>		
	IP protection	NA		
	Anti-vandal	NA		
	Auto brightness	YES	Auto brightness control	
	Direct sunlight	NA		
Certification	CE / FCC			

# MECHANICAL DRAWINGS:

