1U SINGLE SLIDE RAIL CONSOLE DRAWER - MEETS EIA310C & IEC-3

1U, Single Slide Rail, 17.3" 1920x 1080 LCD keyboard Drawer
16 ports PS2 or Combo KVM Switch

Model: YVPW1700HD-S16e

FEATURES:

- Built-in rail self-locking device ensures stability.
- Industrial-grade keyboard with integrated touchpad.
- Effortless PC selection via front push buttons, hotkeys, or on-screen display.
- 1U rackmount with a single slide rail and 17.3" LCD monitor, 521mm depth.
- Secure key-locking mechanism prevents unauthorized access.
- Allows up to 130-degree monitor rotation for enhanced viewing flexibility.
- Console equipped with a 16-port PS/2 or combo KVM switch.
- Tempered glass protects the LCD screen.
- KVM Cable Length Option: 1.8m/ 3.0m/ 5.0m

PS2 KVM Switch

PS2 KVM Cable

Combo (PS2&USB) KVM Switch

UBS KVM Cable

SPECIFICATIONS:

Drawer Design	19" rackmount, 1U, Single slide rail for extraction of both panel and keyboard	
Weight	11 kgs	
Dimension	442.4 x 44 x 521 mm (W x H x D)	
Power Supply	Built-in 60W, 90~264VAC Auto Switch, Operating Temp.: -20~70°C **(Option: 80W, 24~48VDC)**	
Construction	Heavy-duty steel	
Keyboard	Industrial keyboard with touchpad	
Physical Security	Key locking Mechanism	
Protection	Tempered glass protect LCD screen	
Power Consumption	3 watts stand-by, 25 watts in-use	
Display		
LCD Size	17.3"	
Resolution	1920x 1080 **(Option: 1600x 900 Resolution)**	
KVM Switch	• KVM Switch: PS2 KVM or Combo (PS2 & USB) KVM • Port Connection: 16-Port DB-15 • Port Expansion: Daisy Chain up to 8 levels to support 64 servers • Port Selection: 8x Front Push Buttons, OSD Menu, Hotkey • Power Connector: 1x 3-prong AC Socket • Switch Reset: 1x push button • Switch Power: 1x Rocker Switch • Switch LCD on/off: 1x Front standby Push button • Switch LCD control: 4x LCD Adjust push button • LED Port Status: 8x Operation, 8x Power, • LED Key Status: 1x Num Lock, 1x Cap Lock, 1x Scroll Lock	• 16 port PS2/ COMBO PS2/USB KVM with military industrial grade production • Support Password protection and Server name • Support extra daisy chain port and no waste server port for expansion • Support Windows, DOS, Netware, Unix, Linux, Mac and Sun Micro Systems • Hot Plug- add or remove connected computer without powering off • No software required. Selection via Front Push Button, Hot Key, OSD menu • Support PS/2 or USB (COMBO) cable to PC • Auto Scan mode. Easy to monitor Server Operation • Superior Video Bandwidth unto 200MHz • Keyboard status restored when switching computers • LED display for status monitor • Buzzer sound for Server switched confirmation

Environment	**Operating**	**Non-Operating**
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	0%~90%	0%~90%
Approval	CE, FCC, RoHS	

Specifications subject to change without notice, not responsible for typographical errors.

i-Tech Company LLC
EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com

Modified Date: 03-28-2025

MECHANICAL DRAWINGS:

This is subject to change without Notice. Final Drawings will be provided for Approval after Order.

DRAFT

Drawing No.: YVPW1700HD-S8e-03282025-V1