

RUGGED MILITARY GRADE LCD 12 PORTS DVI LCD KVM SWITCH

1U 17" Rackmount Rugged LCD Keyboard drawer 1280 x 1024, 350nits, Sealed 104-keys IP65 silicone keyboard and touchpad with backlight, Front EMC glass, 25"/635mm Deep 12 port DVI-D (support only DVI signal) Noted: Included Power cables only, no DVI and USB cables + With 2 x USB in the front (for external KB/MS) Internal power supply with universal / Auto-Sensing, 100-240V AC 50/60Hz via 4 pins lock connector

Model: AMil-1700-D12e-AC




USB port for Keyboard/Mouse

FEATURES

- Meet MIL-STD-810F/G standard
- 1U 17" LCD Console Drawer, wide operation temperature support 1280 x 1024 resolution
- Build-in 12 port DVI-D KVM switch
- Additional two USB console ports to add local KB/MS (front)
- Sealed 104-keys IP65 silicone keyboard and touchpad with backlight
- MIL connector for power input
- Self-locking and auto release rails for ultra convenience

OPTION

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen



Rear of AMil-1700-D12e-AC

SPECIFICATIONS

Direct no. of Computers		12
KVM Connectors		12
LCD	Size	17"
	Backlight	LED
	Resolution	1280 x1024
	Max.color	16.7M
	Luminance	350cd/m2
	View Angel (H/V)	170 / 160
	Contrast Ratio	1000 : 1
Port Selection		Push Button, Hotkey
USB Local Console		Yes, front USB x 2 for Keyboard / Mouse
KB/Mouse Emulation		USB
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)
Power		100-240V AC 50/60Hz via 4 pins lock connector
Environment (MIL-STD-810G)	Operation temp: -20 to 70°C	(MIL-STD-810, Method 501.5 & 502.5)
	Storage temp: -30 to 80°C	(MIL-STD-810, Method 501.5 & 502.5)
	Humidity: 5% - 95%, non-condensing	(MIL-STD-810, Method 507.5)
	Shock/Vibration: Procedure VI, 50G @ 11ms	(MIL-STD-810, Method 516.6)
	Altitude: 10,000 ft Operational, 30,000 ft Storage	(MIL-STD-810, Method 500.5)
Physical Dimensions / Net Weights		TBD
Packing Dimensions /Gross weights		TBD
Accessories		
1 x 1.8 Power Cord with lock connector		
Option Relate Item		
ADV16	1.8meter DVI-D Cable	
ASU-018	1.8meter USB Cable	

**Specifications subject to change without notice, not responsible for typographical errors.*

PICTURES

