

RUGGED MILITARY GRADE LCD KVM SWITCH




1U 19" 1280 x 1024 LCD Console Drawer Rugged Military Grade 16 ports, Wide Temp, support VGA-USB & VGA-PS/2

Model: AMil-1900-S16e



FEATURES

- Meet MIL-STD-810F/G standard
- 1U 19" LCD Console Drawer, wide operation temperature support 1280 x 1024 resolution
- Bulid-in 16 port combo KVM switch, support VGA-USB & VGA-PS/2.
- Sealed 104-keys IP65 silicone keyboard and touchpad with backlight
- MIL connector for power input
- Self-locking and auto release rails for ultra convenience
- Port selection via push buttons or On-Screen-Display (OSD)




Rear of AMil-1900-S8e/ AMil-1900-S16e

OPTION

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen

OPTIONAL REMOTE IP ACCESS

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



SPECIFICATIONS

| | | |
|------------------------------------|--|-------------------------------------|
| Direct no. of Computers | 16 | |
| KVM Connectors | 240 (Daisy Chain) | |
| LCD | Size | 19" |
| | Backlight | LED |
| | Resolution | 1280 x 1024 |
| | Max.color | 16.7M |
| | Luminance | 450cd/m2 |
| | View Angel (H/V) | 170 / 160 |
| | Contrast Ratio | 1000 : 1 |
| Port Selection | Push Button, Hotkey | |
| Expansion Slot | Yes, option for Remote IP Access | |
| KB/Mouse Emulation | USB & PS2 | |
| Rack Depth | 500mm to 1100mm (rack cabinet front rails to rear rails) | |
| Power | 100-240V AC 50/60Hz via 4 pins lock connector | |
| Environment (MIL-STD-810G) | Operation temp: -20 to 70°C | (MIL-STD-810, Method 501.5 & 502.5) |
| | Storage temp: -30 to 80°C | (MIL-STD-810, Method 501.5 & 502.5) |
| | Humidity: 5% - 95%, non-condensing | (MIL-STD-810, Method 507.5) |
| | Shock/Vibration: Procedure VI, 50G @ 11ms | (MIL-STD-810, Method 516.6) |
| | Altitude: 10,000 ft Operational, 30,000 ft Storage | (MIL-STD-810, Method 500.5) |
| Physical Dimensions / Net Weights | 482x42x660mm (WxHxD) /14KG | |
| Packing Dimensions / Gross weights | 890x180x740mm(WxHxD) /20KG | |

Accessories

1 x 1.8 Power Cord with lock connector

Option Relate Item

| | | | |
|-------|-----------------------------------|-------|------------------------------------|
| AB-6 | 1.8meter 2-in-1 KVM Cable-USB&VGA | AD-6 | 1.8meter 3-in-1 KVM Cable-PS/2&VGA |
| AB-10 | 3.0meter 2-in-1 KVM Cable-USB&VGA | AD-10 | 3.0meter 3-in-1 KVM Cable-PS/2&VGA |
| AB-15 | 5.0meter 2-in-1 KVM Cable-USB&VGA | AD-15 | 5.0meter 3-in-1 KVM Cable-PS/2&VGA |

*Specifications subject to change without notice, not responsible for typographical errors.

MECHANICAL DRAWINGS

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

