RUGGED MILITARY GRADE LCD KEYBOARD DRAWER

1U 17.3" Rackmount Rugged LCD Keyboard drawer 1920 x1080, Support up to 1920 x 1200, 400nits, Sealed 104-keys IP65 silicone USB only keyboard and touchpad with backlight, Front EMC glass, with 16 ports DB-15 combo KVM switch + Internal power supply with universal / Auto-Sensing, 100-240V AC 50/60Hz via IEC Type Power cord

482x42x600mm (WxHxD) /13.5KG

Operating temp: 0 ~ 70C

Storage temp: -30 ~ 75C

Model: AMil-W1730-S16e-IEC

FEATURES

- Complies with the MIL-STD-810F/G standard
- 1U 17.3" LCD Console Drawer, featuring support for 1920x1080 resolution
- Capable of supporting up to 1920 x 1200 resolution
- Equipped with a built-in 16-port combo KVM switch, supporting both VGA-USB and VGA-PS/2
- Features a sealed 104-keys IP65 silicone keyboard and backlit touchpad
- Incorporates self-locking rails with auto-release for enhanced user convenience
- Port selection can be done via push buttons or On-Screen-Display (OSD)

OPTIONAL REMOTE IP ACCESS

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.

OPTION

- DC 9~36V power input
- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen



Rear of AMil-W1730-S16e-IEC

SPECIFICATIONS

Direct no. of Computers		16	
KVM Connectors		240 (Daisy Chain)	
LCD	Size	17.3”	
	Backlight	LED	
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)	
	Max.color	16.7M	
	Luminance	400cd/m2	
	View Angel (H/V)	160 / 140	
	Contrast Ratio	600 : 1	
Port Selection		Push Button, Hotkey	
Expansion Slot		Yes, option for Remote IP Access	
KB/Mouse Emulation		USB & PS2	
Rack Depth		600mm to 1000mm (rack cabinet front rails to rear rails)	
Power		100-240V AC 50/60Hz via IEC Type Power Cord	
Environment (MIL-STD-810G)		Operation temp: 0 to 70°C	(MIL-STD-810, Method 501.5 & 502.5)
		Storage temp: -30 to 75°C	(MIL-STD-810, Method 501.5 & 502.5)
		Humidity: 10% - 90%, non-condensing	(MIL-STD-810, Method 507.5)
		Shock/Vibration: Procedure VI, 50G @ 11ms	(MIL-STD-810, Method 516.6)
		Altitude: 10,000 ft Operational, 30,000 ft Storage	(MIL-STD-810, Method 500.5)
Physical Dimensions / Net Weights		482x42x600mm (WxHxD) /13KG	
Packing Dimensions / Gross weights		720x160x860mm(WxHxD) /19KG	
Accessories			
1 x 1.8 Power Cord			
Option Related Items			

AB-6	1.8meter 2-in-1 KVM Cable-USB&VGA	AD-6	1.8meter 3-in-1 KVM Cable-PS/2&VGA
AB-10	3.0meter 2-in-1 KVM Cable-USB&VGA	AD-10	3.0meter 3-in-1 KVM Cable-PS/2&VGA
AB-15	5.0meter 2-in-1 KVM Cable-USB&VGA	AD-15	5.0meter 3-in-1 KVM Cable-PS/2&VGA

Specifications subject to change without notice, not responsible for typographical errors.