## **RACK MOUNT DUAL LCD DISPLAY DRAWER**



2U 17.3" 1920x1080 Widescreen Dual LCD Rackmount LCD Keyboard Console Drawer 2x HDMI and SDI Port 104-key keyboard with Touch Pad Mouse Self-locking and auto release rails for ultra convenience and built in speakers, 630mm . Shipping weight 42lbs

### Model: ARP2D1730-SDI



#### **FEATURES:**

- 2U foldable dual 17.3 inch widescreen LCD display Drawer
- Dual HDMI & SDI Port
- 1920 x 1080 high resolution
- Support FHD with 1080p resolution.
- Build in 2x 2 watts speakers
- Independent front OSD Control buttons to optimized display
- Hidden & Independent retractable tray for ultra convenience

#### **SPECIFICATIONS**

| LCD Characteristics : |               |  |
|-----------------------|---------------|--|
| Screen Size           | Dual 17.3"    |  |
| Backlight Type        | LED           |  |
| Resolution            | 1920*1080     |  |
| Contrast Ratio        | 400:1         |  |
| Brightness ( cd/m2 )  | 300           |  |
| View Angles (H/V)     | 140/120       |  |
| Pixel Size ( HxV ) mm | 0.1989x0.1989 |  |
| Max. Color            | 262K          |  |

| Input Signals: |  |
|----------------|--|
| HDMI           | Dual HDMI Connector                    |
| SDI            | Dual SDI_IN and SDI Loop Out Connector |
| Power Input    | Standard IEC Inlet                     |

# Power Specifications : AC Power Input Standard IEC Type Power Cord with Internal Power adapter, 100-240V AC Input Wide Range DC Power Input ( option ) Screw Type Terminal Block with internal wide Range DC 9-36V power module

\*Specifications subject to change without notice, not responsible for typographical errors.

| ⇒        |                |
|----------|----------------|
| HOM SOLT | зохолт ном 🖉 🔿 |

| User Controls Interface:          |  |
|-----------------------------------|--|
| Power ON / OFF via Front Button   |  |
| Power Mode Status LED indicator   |  |
| OSD ( On Screen Display ) Buttons |  |

| Mechanical and Environment: |  |  |
|-----------------------------|--|--|
| Height                      | 2U Foldable                                |  |
| Rack Depth                  | 600 to 1000mm ( cabinet front rail to rear |  |
| Construction                | Metal Housing                              |  |
| Operating Temperature       | 0 - 50 deg. C                              |  |
| Operating Humidity          | 5% - 95% ( non -condensing )               |  |
| Anti-Vibration              | 5 - 500 Hz / 1 Grms PTP                    |  |
| Anti-Shock                  | 15G / Peak ( 11 ms )                       |  |
| Physical Dimension (WxHxD)  | 443 x 67 x 630 (mm)                        |  |
| Packing Dimension (WxHxD)   | 740 x 660 x260 (mm) estimated              |  |
| Net Weight / Gross Weight   | 20 / 24 (KGs) estimated                    |  |
| Certification and Approvals | CE / FCC / RoHs                            |  |





**DRAWINGS:** This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.



