

FEATURES:

- Support combo interface, VGA-USB & VGA-PS/2.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.

OPTIONAL R EMOTE IP ACCESS:

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



SPECIFICATIONS

Direct no. of Computers		8			
Maximum no. of Computers		232(Daisy Chain)			
	Size	19"			
	Backlight	LED			
	Resolution	1280*1024			
LCD	Max. Color	16.7M			
	Luminance	250cd/m2			
	View Angel (H/V)	170 / 160			
	Contrast Ratio	1000:1			
Port Selection		Push Button, OSD or Hotkey			
Expansion Slot		Yes, option for Remote IP Access			
KB/Mouse Emulation		USB & PS2			
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)			
Power		Built in DC 125V Power (72-144VDC in)			
Environment		Operation temp: 0 to 50° C Storage temp: -20 to 60° C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP			
Physical Dimensions / Net Weights		448x42x580mm (WxHxD) / 12.5KG			
Packing Dimensions / Gross weights 715x140x780mm (WxHxD) / 19KG					
Accessory					
1.8meter	1.8meter IEC Type Power Cord (1.8meter VGA& PS2Cable + 1.8meter USB A Type Cable for AVP117e/119e				

Option Rel	ate Item		
AB-6	1.8meter 2-in-1 KVM Cable-USB&VGA	AC-6	1.8meter 3-in-1 KVM Cable-PS/2&VGA
AB-10	3.0meter 2-in-1 KVM Cable-USB&VGA	AC-10	3.0meter 3-in-1 KVM Cable-PS/2&VGA
AB-15	5.0meter 2-in-1 KVM Cable-USB&VGA	AC-15	5.0meter 3-in-1 KVM Cable-PS/2&VGA
AIP101	KVM over IP module for Remote Bios Level Access	•	

i-Tech Company LLC TOLL FREE: (888) 483-2418 • EMAIL: <u>info@itechlcd.com</u> • WEB: <u>www.iTechLCD.com</u>

DRAWINGS

