

1U Portable Style Rackmount

1U 15.6" 1920 x 1080 LCD, all aluminum construction with bumper at the corner, portable style, HDMI input, USB port for Keyboard & mouse + CAT5 VGA USB KVM Extender x 1

Model: AVPW1560C1e



With iTech Company's AVPW1560C1e, you are now able to simplify IT duties with an easy-to-install monitor and keyboard for your server set up. This is a great solution for interfacing with server racks while eliminating the limitations of a stationary rack-mounted KVM. It is ruggedly built and can endure harsh environment operations. It is also lightweight and easy to carry, with fold and lock design for convenient storage anywhere.

Remotely Control Computers

Sometimes, there is no room for a server or you want to put all your computers in a safe place. Set your AVPW1560C1e at a convenient and suitable control field over an already existing network construction. With this unit, you can remotely control systems up to 500 feet away.

FEATURES


- 1 standard VGA USB CAT5 Extender
- Compact size and lightweight design with fold and lock mechanism
- High resolution for crisp and clear display
- No software needed
- 105-key cherry switch keyboard with touchpad

SPECIFICATIONS

Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
Aspect Ratio / Size	Wide /15.6" viewable diagonal area
Active Area / Pixel Pitch	344.16(H) x193.59(V) mm / 0.1793(H) x 0.1793(V) mm
Native Resolution / Colors	1920(H) x1080(V)/16.7M
Brightness / Contrast	250 cd/m ² (typ) / 500 : 1
Response Time	< 12 ms
Viewing Angle (typical)	H.90° (- 45° - + 45°) , V. 65°(- 40° - + 25°)
Light Source	LED backlight, Long life, 35,000 hrs (typ)
Power input	9~36V DC and provide a cable with DC jack and + - wire
Estimate power consumption	Around 20 Watts (operating mode), 1 Watts (power saving mode).

**Specifications subject to change without notice, not responsible for typographical errors.*

POWER CORD with (+ -) Wire




CAT6 KVM Extender Transmitter & Receiver 150/300 meter (500/1000 feet)

FEATURES

- Remote console up to 150M / 300M (500 /1000 feet) away with superior auto-adjust RGB signal capability
- Dual user access at remote side, support USB/PS2 combo
- Switch computers by push button or hot key commands
- Audible feedback when switching
- LED indicators for computer status or data transmission
- Pure hardware solution makes network independent
- Plug-and-Play , no software required

Transmitter

Receiver



	Transmitter	Receiver
USB Connector	2 x USB for KB& Mouse	
DB-15 Connector	1 for VGA Monitor, 1 for VGA & Combo KB/ Mouse	
RJ-45 Connector	8P8C	
LEDs	2 (Power / on line)	2 (Local / Remote)
Port selection	N/A	Hot key / Push button
Security	User name and Password	
OSD	Hotkey , Status	
VGA Resolution (Local Host)	1920x1440	
VGA Resolution (Remote Host)	1280 x 1024 /1024 x 768	
Housing	Metal	
Power	100-240VAC, 50/60HZ via AC/DC cord	
Operation Temperature	0 to 50 °C	
Storage Temperature	-20 to 60°C	
Humidity	90%,non-condensing	
Certificated	CE/FCC	
Dimension		
Weight		

DRAWINGS

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

