

1U RACKMOUNT COMBO DB15 KVM SWITCH


1U Rackmount 8-ports Support combo interface VGA-USB
110VDC (Rack depth increase 100mm, total of 144mm)
KVM cables are not included.

Model: AVS801-110DC



FEATURES:

- Capable of connecting 8 servers in 1U.
- Support combo interface VGA-USB & VGA-PS/2.
- USB local console, optional remote IP console.
- Cascade up to 8 levels, support mixed CAT6 & DB15 Combo KVM switch.
- Mixed PS2/USB/SUN & MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.



Rear of AVS801-110DC

SPECIFICATIONS

No. of Computers	8
Max. no. of Computers	232 (Daisy Chain)
KVM port connector	HD DB15 Female
Local Console	1x HD DB15 for VGA (up to 1920x1440 resolution) 2x USB Type A for KB / Mouse
Daisy Chain	1x DB15 (Female), up to 8 levels
Hot keys	Scroll-Lock, Caps-Lock, Num-Lock, Alt-Ctrl-Win
Compatibility	Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix
Power	Internal 72~144VDC power module with screw type terminal block
Environment	Operation temp.: 0 to 50°C Storage temp.: -20 to 60°C Humidity: 10% - 90%, non-condensing
Physical Dimensions / Net Weights	482mm (W) x 246.5 mm (D) x 44mm (H) / 5kg
Packing Dimensions / Gross Weights	560mm (W) x 330mm (D) x 120mm (H) / 8kg <i>estimated</i>

Cable options

AB-6	1.8meter 2-in-1 KVM Cable - USB & VGA	AD-6	1.8meter 2-in-1 KVM Cable – PS/2 & VGA
AB-10	3.0meter 2-in-1 KVM Cable - USB & VGA	AD-10	3.0meter 2-in-1 KVM Cable – PS/2 & VGA
AB-15	5.0meter 2-in-1 KVM Cable - USB & VGA	AD-15	5.0meter 2-in-1 KVM Cable – PS/2 & VGA