

RUGGED COMPLETELY SEALED FULL IP66/NEMA4X STAINLESS STEEL CHASSIS/SURFACE MOUNT

21.5" Industrial Panel / 1920x1080 / 250nits, Stainless 304 Enclosure with Full IP66,
P-CAP Touch with True Flat Design, Fanless, JNC8H-H310 / i5-8500T
(9M Cache, up to 3.5GHz) / RAM 4GB / SSD 256GB

I/O (all connectors are waterproof connectors / 6ft long) : VGA x1, LAN x1
COM x1, USB x1 (rear side), USB x1 (front side) and 24VDC
Power Adapter Input, Win 11 Pro 64bit

Model: CCHW2150SIP-i5-FPCAP-DCV2

FEATURES:

- High Contrast color LCD Monitor with resolution up to Full HD (1920x1080)
- Stainless 304 Enclosure with Full IP66
- JNC8H-H310 / i5-8500T (9M Cache, up to 3.5GHz)
- RAM 4GB / SSD 256GB
- Win 11 Pro 64 bit
- High Shock & Vibration Resistance
- Widely Application: Automation, Medical, Tourist, Transportation

SPECIFICATIONS:

Display	Viewing Size Image	21.5"
	Pixel Pitch (mm)	0.248 x 0.248
	Resolution	1920 x 1080
	Contrast Ratio	5000 : 1 (typ.)
	Color	16.7M (8bits/colors)
	Brightness	250 cd/m ²
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA
Power	Source	24 VDC
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP
	High Brightness	YES
	Auto Dimming	YES
	POWER in	DC24V, DC9V~36V
	Remote Control	YES
	IO	AV,HDMI, DVI, DP

**Specifications subject to change without notice, not responsible for typographical errors.*

APPLICATIONS:




JNC8H-IH310 MOTHERBOARD



1. Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (Max 65W)
2. Intel® Coffee Lake-S H310 Chip support 9th CPU
3. Support Single Channel DDR4 2133MHz, up to 64GB
4. Realtek ALC662VD Audio
5. 1* Intel® I219-V + 1* Intel® i211AT GbE
6. 1* SATAIII (6Gb/s) & M.2 (M key 2242)
7. HDMI/VGA /EDP (CO-lay LVDS) Output
8. 4* RS232 (COM1/2 Support 5V/12V TTL), 4* External USB3.0, 5* Internal USB2.0
9. 1* PCIe x4 Slot, 1* M.2 E key Support CNVi
10. DC 12~24V Input
11. Thin MINI ITX Form Factor (170 *170 mm)

INTERNAL DIAGRAM




SPECIFICATIONS

Form Factor	
Dimensions	- Thin Mini ITX (170 * 170mm)
Processor System	
CPU	- Intel® LGA1151 Series Processor (Max. 65W)
Core Number	- by CPU
Max Speed	- by CPU
L2 Cache	- by CPU
Chipset	-H310
BIOS	-AMI 128M Flash ROM
Expansion Slot	
M.2	-1 (E key 2230,Support CNVi) -1 (M Key 2242)
SATA	-1
PCI-e	-1 * PCI-E x4 slot
Memory	
Technology	- Single channel DDR4 2133MHz DRAM
Max.	-64GB
Socket	-2*SO-DIMM
Graphics	
Controller	- Intel® HD Graphics
VRAM	- Shared Memory
VGA	-1 (Max. Resolution: 1920x1200@60Hz)
LVDS	-1 (Co-lay eDP, Max. Resolution: 1920x1080@60Hz)
eDP1.3	-1 (Co-lay LVDS, Max. Resolution: 4096x2304@60Hz)
HDMI 1.4	-1 (Max Resolution : 4096x2160@30Hz)
Multi Display	- Dual Display
Ethernet	
Ethernet	-10/100/1000 Mbps
Controller	- Intel® I219-V + i211AT Gigabit LAN
Connector	- 2* RJ 45
Audio	
CODEC	- HD Audio : Realtek ALC662VD
Channel	- Line-Out, MIC
SATA	
Max Data Transfer Rate	-1* SATA 1 (6.0Gb/s)
Rear I/O	
VGA	-1
HDMI	-1
Ethernet	-2
USB	- 4* USB 3.0
Audio	-1 (Line-out, MIC)
DC-input	-1

Internal Connector	
USB	-5 (USB 2.0)
PS/2	-1
LVDS / inverter	-1 (Co-lay eDP)
eDP	-1
Serial	- 4 (COM1/2 Support 5V/12V TTL)
SATA	-1* SATA 1 (6.0Gb/s)
M.2	- 2 (M key + E key)
GPIO	-1 (8 bit)
Chassis intrusion	-1
Audio Header	-1
SMBUS/I2C	-1
AT mode	-1
Watchdog Timer	
Output	- From Super I/O to drag RESETCON#
Interval	- 256 segments (IOsec ~ 255min)
Power Requirements	
Input PWR	-12 ~ 24V DC-in
Power On	- AT/ATX Supported - AT : Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Certifications	
Certifications	- CE, FCC, RoHS, REACH
Environment	
Temperature	- Operating: 0°C~60°C
	- Storage: -20°C~85°C
Warranty	
Warranty	- 2 Years Limited Warranty
Packing	
Packing	-Net Weight: -Gross Weight: -Color Box dimension: 362*290.5*65mm

MECHANICAL DRAWINGS

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.



Drawing No.: CCHW2150-SIP-i5-FPCAP-DCV2-06222023-V1