

27" High Brightness 1000nits based on Default 3 set waterproof connectors Waterproof connectors & cables: HDMI, VGA & Power 6ft long only with external 100~240V AC + adapter Wide Temp -30 ~ 85C Operating Temp

Remark: This unit designed to be installed under completed shaded area without direct sunlight. Not facing east and west



Model: CCHW2700HB-SIP

FEATURES:

- High Contrast color TFT LCD Display support resolution up to Full HD.
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Full IP66 Stainless Design.
- Universal Power adapter.
- Auto Power On: Monitor is always "ON" when connect to power.
- Auto Video Signal On: Monitor (Backlight) will turn off when no video signal, but it will Auto turn back on.

SPECIFICATIONS:

Display	Viewing Size Image	27"
	Active Display Area (mm)	599 (H) x 337.50 (V)
	Pixel Pitch (mm)	311.25(H)x311.25(V)
	Resolution	1920x1080
	Contrast Ratio	3000 : 1 (typ)
	Color	16.7M (8bits/color)
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Brightness	1000 cd/m2
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	HDMI + VGA
Power	Source	AC100V~AC240V
	Consumption	45W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	PCAP,IR
	High Brightness	1500
	Auto Dimming	YES
	POWER in	DC24V
	Remote Control	YES
	IO	AV, DP, DVI

**Specifications subject to change without notice, not responsible for typographical errors.*

MECHANICAL DRAWING:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

