

PANEL/FLUSH MOUNT (Metal-5mm) LCD MONITOR

Panel/Flush Mount (Metal-5mm), 15" LCD monitor, 1024 x 768, 350nits, VGA/DVI-D Input, Power input DC12V external 100-240V Power adapter, Rear OSD, including rear screw/Clamp/VESA Mount. ***Non Touch ***. Front bezel 15" W x12" H, Cut Out 14.15"Wx10.54". Thickness 1.92"

MODEL: CPM1500-RE1



FEATURES:

- Panel/Flush Mount (Metal-5mm)
- VGA/DVI-D Input, Rear OSD
- Rear Screw/Clamp/VESA Mount
- Resolution: 1024x768
- Brightness: 350nits

SPECIFICATIONS:

Panel Size	15"
Active Display Area(mm)	305.80(H)x229.70(V)
Resolution	1024x768
Brightness(cd/m2)	350 (Typical)
Contrast Ratio	700:1 (Typical)
Viewing Angles(CR>=10 L/R/U/D)	-80~80(H) ; -70~70(V)
Display Colors	16.2M (6 bits/color)
Standard Input Signal	1 x VGA 1 x DVI-D
Touch Screen(Optional-1)	Resistive Touch Protective Glass
Touch Screen(Optional-2)	SAW Touch (Surface Acoustic Wave)
Audio / Speakers (Optional)*	Audio line in (3.5mm) + Speaker x2
OSD	5 Keys: -, +, Power, Esc, Enter
Power Input	DC12V external 100-240V Power Adapter
Power Consumption	15W typical, Normal operation
Operating temperature	0~50°C
Storage Temperature	-10~60°C
Accessories	Power AC-DC Adapter(100V~240V) VGA cable (1.8m)

I/O Optional	
Optional 1*	1 x VGA (D-sub 15) 1 x HDMI (Type-A) 1 x DVI-D
Optional 2*	1 x VGA (D-sub 15) 1 x DVI-D 1 x S-Video 1 x Composite

**Specifications subject to change without notice, not responsible for typographical errors.*

MECHANICAL DRAWING:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

