

FEATURES:

- 10.4" Industrial Panel / 1024x768 / 350nits
- Stainless Steel 304 Enclosures with Full IP66 / Wall mount
- AR Glass / Rear OSD Design
- I/O (all connectors are IP67 waterproof connectors / 6ft long) : VGA, BNC female (I/P), BNC female (O/P) and 12VDC Power Adapter

SPECIFICATIONS:


	Viewing Size Image	10.4"
	Active Display Area (mm)	213 (H) x 159.50 (V)
	Pixel Pitch (mm)	0.2055 (H) x 0.2055(V)
	Resolution	1024 x 768
Display	Contrast Ratio	1400 : 1 (typ.)
Display	Color	16.7M(8 bits/colors)
	Brightness	350nits
	Viewing Angle	-89~89(H) ; -89~89 (V)
	Recommended Resolution	1024 x 768 @ 60H, 75Hz
	Signal Connector	VGA, BNC Female (I/P), BNC female (O/P)


Power		Source	12VDC Power Adapter
	Power	Consumption	6.0W typical, normal operation
		Management	VESA DPMS Compliant


^{*}Specifications subject to change without notice, not responsible for typographical errors.


MECHANICAL DRAWING:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.









Drawing No.: ECH1040XC-SIP-BNC-O-10272025-V1



i-Tech Company LLC

EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com