

FULL IP66 / NEMA4X STAINLESS STEEL CHASSIS DISPLAY



RUGGED COMPLETELY SEALED FULL IP66 LCD DISPLAY

55" Industrial Panel / 1920x1080 / 450nits SUS 304 Enclosures with Full IP66
Wall Mount, PCAP Touch, DVI, HDMI, USB (for Touch use), RS232 and
100-240VACV Power Input



Model: SCHW5500SFTC

FEATURES:

- SUS 304 Enclosures
- 55" Industrial Panel / 1920x1080 / 450nits
- SUS 304 Enclosures with Full IP66 / Wall Mount
- Vandal Proof Film Bonding on 4mm PCAP Touch
- Eye Bolt x 3 / RS232 command code for Remote Control
- I/O (all connectors are waterproof connectors / 6ft long): DVI, HDMI, USB (for Touch use), RS232 and 100-240VACV Power Input

SPECIFICATIONS:

Display	Viewing Size Image	55"
	Active Display Area (mm)	1211.60 (H) x 682.60 (V)
	Pixel Pitch (mm)	0.21(H)x 0.63(V)
	Resolution	1920x1080
	Contrast Ratio	4000 : 1 (typ.)
	Color	1073.7M (10bits/color)
	Brightness	450nits
	Viewing Angle	-89~89 (H) ; -89~89(V)
	Recommended Resolution	1920 x 1080 @ 60Hz
Power	Source	100-240VACV Power Input
	Consumption	170W typical, normal operation
	Management	VESA DPMS Compliant

**Specifications subject to change without notice, not responsible for typographical errors.*

MECHANICAL DRAWING

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

