

Sunlight Readable LCD LED Open Frame




15" Sunlight Readable LCD LED Open Frame

Model: JOP1500HB-B

Features

- Sunlight Readable
- High Contrast Ratio
- Wide Temperature
- Low Power Consumption
- Optional Touch Systems
- VGA to XGA

Model: JOP1040HB-B



Specifications:

Display Type	Open Frame
LCD Display	15" TFT LCD Module
Base Panel Supplier	AUO
Base Panel Model	G150XG03 V2
Display Color	8-bits, 16.2M/262K colors
Display Area	304.128 x 228.096 mm
Brightness	1,500 nits
Resolution	1024 x 768 (SVGA)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.297 x 0.297
Viewing Angle	70°/70°(H) 65°/60°(V)
Response Time	8ms (Tr+Tf)
Sync	LVDS
Power Consumption	TBD
Temperature	Operation 0°C~+65°C Storage -20°C~+65°C
Dimension(WxHxD)mm	326.50 x 253.50 x 12.00
Lamp Lifetime (HR)	50,000
Control(AD) Board (Optional)	None
OSD Button	None
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...
LED Driver	JL150
Weight	1,010 g
Optional	Transflective tech Glass Bonding Touch

Specifications are subject to change without notice

Control(AD) Board (Optional)	Standard VGA + DVI + Audio(Optional) Option VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key Power Switch Select(+,-) Down Up Menu

