

Sunlight Readable LED LCD Kits


15" Sunlight Readable LED
LCD kits

Model: JPD1500-KIT-A



Features

- Sunlight Readable
- High Contrast Ratio
- Wide Temperature
- Low Power Consumption
- Optional Touch Systems
- VGA to XGA



Specifications:

PANEL

Display Type	LCD + LED Driver + AD/OSD Board
LCD Display	15" TFT LCD Module
Base Panel Supplier	AUO
Base Panel Model	M150XN07
Display Color	6-bits, 16.2M colors
Display Area	304.128 x 228.096 mm
Brightness	1000 nits
Resolution	1024 x 768 (XGA)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.297 x 0.297
Viewing Angle	80°/80°(H) 70°/60°(V)
Response Time	8ms (Tr+Tf)
Sync	LVDS
Power Consumption	TBD
Temperature	Operation 0°C~+50°C Storage -20°C~+60°C
Dimension(WxHxD)mm	326.50 x 253.50 x 12.00
Lamp Lifetime (HR)	50,000
Control(AD) Board (Optional)	N/A
OSD Button	N/A
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...
LED Driver	JL150
Weight	1,110 g
Optional	Transflective tech Glass Bonding Touch

Specifications are subject to change without notice

Control(AD) Board (Optional)	Standard VGA + DVI + Audio(Optional) Option VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key Power Switch Select(+,-) Down Up Menu

