

# IP PUBLIC VIEW MONITOR

13.3" Full HD IP Public View Monitor 1920x1080 LCD  
Input/Output: 1x LAN, 1x HDMI, 1x USB, 1x MicroSD  
1x Alarm (in/out/GND) Camera: 1/2.8" 2MP Sony CMOS, 30FPS

## MODEL: LPM1330



### LAN CONNECTIVITY:

The device offers the option to transmit video through its LAN port or to establish a connection with a computer for communication purposes.

### ON-SCREEN RECORDING TEXT:

Users can select various texts to display on the screen during gameplay to indicate that video recording is in progress, serving as a deterrent.

### ENHANCED SAFETY FEATURES:

The device is equipped with features such as obstruction detection, video loss detection, and motion detection, which significantly enhance security within the surveillance area.

### DIVERSE INTERFACE OPTIONS:

Featuring multiple video and communication interfaces including HDMI, USB, LAN, and a MicroSD card slot.

### THOUGHTFUL OUTLET DESIGN:

The inclusion of an outlet for organizing cables prevents clutter and maintains a tidy setup.

### WEB-BASED REMOTE CONTROL:

Through integration with a network platform, users can remotely modify display images, security settings, and other functionalities of the monitor's video signal.

### ADVERTISING CAPABILITIES:

Apart from serving as a public view monitor, it doubles as an advertising machine with a built-in multimedia player capable of playing commercials and other content seamlessly.

### USB PLAYBACK:

Users have the convenience of playing video, music, and images directly from a USB flash drive.



# RICH INTERFACES

Equipped with a number of video and communication interfaces. For example, HDMI, USB, LAN, MicroSD card slot.



## SPECIFICATIONS

DISPLAY	
Display Screen	13.3"
Physical Resolution	1280x1080
Aspect Ratio	16:9
Brightness	300ntis
Contrast Ratio	800:1
Viewing Angle	170°/70° (H/V)
HDR Supported	HDR10 300/1000/10000
INPUT	
LAN	1 (1000M)
HDMI Input	1
Alarm (Buzzer)	1 (in/out/GND)
USB	1
MicroSD Card Slot	Support up to 1TB
Mini USB	For upgrade
Speaker	2
CAMERA	
Sensor	1/2.8" 2 Megapixel Sony CMOS
Resolution	1920x1080
Frame Rate	30fps
Compression	MPEG, etc.
Color	8bits
Lens	3.0mm (F1.8)
Angle of View	123°H
Distance	>0.2m
Motion Detection	Supported
OTHER	
Input Voltage	DC 12V (PoE supported)
Power Consumption	≤17W (12V)
Operating Temp	0°C ~ 50°C
Storage Temp	-20°C ~ 60°C
Dimension (LWD)	334.6x244x42.9mm
Weight	2.28kg

\*Specifications subject to change without notice, not responsible for typographical errors.

## ACCESSORIES

