



### Main Features

- On-board Intel® Atom™ Dual Core D2550 processor, 1.86 GHz
- Intel® NM10 Express chipset
- 1x DVI-I & 1x HDMI display output
- Dual Intel® 82574L GbE LAN ports
- 2x RS-232/422/485 and 2x RS-232
- 6x USB2.0
- 1x external CFast socket
- 1x mini-PCIe with two antenna holes
- Support 9-36V DC input
- Supports ATX power mode, WoL, LAN teaming and PXE function

### Product Overview

Powered by Intel® Atom™ Dual Core D2550 1.86 GHz and NM10 PCH, NVW1040 has higher graphic and computing performance, but 3 Watts less power consumption compared with previous Atom platform! With performance enhance, NVW1040 still follow NVW guideline with fanless and cables-less concept housed in a compact chassis, 185mm (W) x 131mm (D) x 54mm (H). The NVW1040 offers dual independent display capability through DVI-I and HDMI connectors, Dual Intel GbE LAN ports, 6x USB2.0, 2x RS-232, 2x RS-232/422/485, CFast socket and mini-PCIe socket for optional wireless module connection, either WiFi or 3.5G module.

NVW1040's support for 9-36V DC input enhances its reliability in different power condition in factory automation or machinery automation. With Dual independent display and super graphic performance, the NVW1040 is an idea choice for public information, self-service Kiosk, access control or data acquisition controller...etc.

### Specifications

#### CPU Support

- > On-board Intel® Atom™ Dual Core processor D2550, 1.86GHz, 1ML2 cache
- > Intel® NM10 Express chipset

#### Main Memory

- > 1 x DDR3 SO-DIMM sockets, support up to 4G DDR3 - 800/1066 SDRAM, un-buffered and non-ECC

#### I/O Interface-Front

- > ATX power on/off switch
- > HDD access/ power status LEDs
- > 4x COM ports (COM2& 3: RS2-32/422/485)
- > 2x USB2.0 port
- > Audio jack (speaker-out & Mic-in)
- > 2x antenna holes

#### I/O Interface-Rear

- > 2x Intel® 82574L GbE LAN port
- > 4x USB2.0 port
- > 1x HDMI
- > 1x DVI-I (support VGA & DVI-D display via cable)
- > 1x 2-pin DC input, Support 9-36V DC input
- > 1x external screwed type CFast socket

#### Device

- > 1x 2.5" HDD driver bay
- > 1x External CFast Socket
- > 1 x mini-PCIe socket (support optional Wi-Fi or 3.5G module)

#### Power Requirements

- > Support 9-36V DC input
- > 1x optional 12V, 60W power adapter

#### Dimensions

- > 185mm(W) x 131mm(D) x 54mm(H) (7.28"x 5.2"x 2.13")

#### Construction

- > Aluminum chassis with fanless design


#### Environment

- > Operating temperature:
- > Ambient with air flow: -5°C ~ 55°C (according to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- > Storage temperature: -20°C ~ 80°C
- > Relative humidity: 10% to 93% (non-Condensing)

Model: NVW1040



## Dimensions



- > Shock protection: 20G, half sine, 11ms, IEC60068-2-27
- > Vibration protection
  - Random: 0.5Grms @5~500 Hz according to IEC68-2-64
  - Sinusoidal: 0.5Grms @5~500 Hz according to IEC68-2-6

### Certifications

- > CE approval
- > FCC Class A

