

1-PHASE 208V 20A BASIC PDU

Single phase Basic PDU - Horizontal

- Horizontal 1U
- Outlet : IEC C13 x 12
- 208V / 20A, w/o MCB
- Input cordset : 3m cord (9.8ft) w/ 20A L6-20P plug

MODEL: PD-12C13-20A-L620P

Single phase basic PDU	
Input Rating	20A (16A derated), 208V
Power Capacity	3.3 kVA
Outlet	10A Rated C13 x 12
Inlet	20A NEMA L6-20P plug
Cordset	9.8 feet UL SJT 12 AWG cordset
Protection	Nil
Circuit Details	Output 16A derated, C 13 # 1 - 12

Chassis Material	Steel
Chassis Color	Black
Product Dimension	17.4 (W) x 4.7 (D) x 1.8 (H) inch
Net weight	7.26 lb
Packing Dimension	20.7 (W) x 9.1 (D) x 3.1 (H) inch
PDU gross weight	7.83 lb

EMC Compliance	FCC Part 15 Subpart B (Class A)
Safety Compliance	Tested to UL 60730-1:2016 and CAN /CSA-E60730-1:2015
	Tested to UL62368-1:2014 and CAN / CSA-C22.2 No. 62368-1:2014
Environment Compliance	RoHS3 & REACH
Operating Temperature	-5 to 60 °C
Storage Temperature	-25 to 65°C
Operating Altitude	0 to 2,000 m
Storage Altitude	0 to 15,000 m
Humidity	8 to 95% RH, non-condensing

*Specifications subject to change without notice, not responsible for typographical errors.

MECHANICAL DRAWINGS:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

