

15.6" Android Touch Panel PC, Ultra slim Aluminum Front Bezel, True-flat PCAP Touch, Light and Fanless design with RK3288 Processor 2.0 GB Ram + 8.0 GB eMMC on board.



MODEL: TNW1560-AO

SPECIFICATIONS:

| | | |
|---------------------------|-----------------------------------|---|
| System | Processor | ARM Rockchip RK3288, Quad-Core Cortex-A17, up to 1.8 GHz |
| | System Memory | Dual Channel DDR3L-1333, 1/2/4 GB, on board |
| | Storage Device | 1 x eMMC 8/16/32/64/128G, 1 x TF Card slot |
| | GPIO | 4 x Programmable GPIO |
| LCD Touch Panel | LCD Size | 15.6" |
| | Brightness | 220 nits (1000 nits optional) |
| | Resolution | 1366 x 768 or 1920 x 1080 (Optional) |
| | Touch Screen | True-Flat PCAP Touch (IP67 Front) |
| Expansion | Others | 1 x IR, 1 x I2C, 1 x MIPI CSI Camera, 1 x Upgrade button, Support RTC, Temperature Sensor |
| | | |
| External I/O Ports | USB | 2 x USB 2.0, up to 7 x USB 2.0 (Optional) |
| | Serial Port | 2 x RS-232, 1 x TTL |
| | LAN | 1 x Giga LAN, 1 x Wifi+BT (Wifi IEEE 802.11 b/g/n, 2.4GHz, BT4.0) |
| | Display | 1 xHDMI, 1 xLVDS, 1 x eDP |
| Audio | Internal Speaker | 2x Stereo speaker (Optional) |
| Power | Power Supply Connector | Power adapter DCIN Input: 12V, Connector type: 1x Phoenix connector |
| Environment | Ventilation Dust & Water Proof | Fanless Front IP67 |
| | Operating Temperature | 0~60°C (32~140°F) |
| | Storage Temperature | -20~70°C (-4~176°F) |
| | Humidity | 5% ~ 95% R/H, non-condensing |
| Dimensions | | 396.81 x 247.12x42 mm |
| Weight | | 2.4 kg |
| Mounting | | VESA Moun, Panel Mount with Panel Mount bracket (Optional) |
| OS Supported | | Android 5.1 /7.1 /8.1 /9.0, Linux |

**Specifications subject to change without notice, not responsible for typographical errors.*



MECHANICAL DRAWING:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

