

Panel Mount 15.6" 1920x1080 Android Touch Panel PC, Ultra Slim Aluminum Front Bezel, True-flat PCAP Touch, Light and Fanless Design with RK3288 Processor, 2.0 GB Ram + 8.0 GB eMMC on board. with 1000nits brightness, Anti-UV, Anti-IR Protection for the touch

**MODEL: TNW1560HB-AO**



## SPECIFICATIONS:


<b>System</b>	Processor	ARM Rockchip RK3288, Quad-Core Cortex-A17, up to 1.8 GHz
	System Memory	Dual Channel DDR3L-1333, 2GB on board as default
	Storage Device	1 x TF Card slot, 8GB eMMC on board as default
	GPIO	4 x Programmable GPIO
<b>LCD Touch Panel</b>	LCD Size	15.6"
	Brightness	1000 nits
	Resolution	1920x1080
	Touch Screen	True-Flat PCAP Touch (IP67 Front), Anti-UV, Anti-IR protection
<b>Expansion</b>	Others	1 x IR, 1 x I2C, 1 x MIPI CSI Camera, 1 x Upgrade button, Support RTC, Temperature Sensor
<b>External I/O Ports</b>	USB	2 x USB 2.0, up to 7 x USB 2.0 (Optional)
	Serial Port	2 x RS-232, 1 x TTL
	LAN	1 x Giga LAN, 1 x Wifi+BT (Wifi IEEE 802.11 b/g/n, 2.4GHz, BT4.0)
	Display	1 xHDMI, 1 xLVDS, 1 x eDP
<b>Audio</b>	Internal Speaker	2x Stereo speaker (Optional)
<b>Power</b>	Power Supply Connector	Power adapter DCIN Input: 12V, Connector type: 1x Phoenix connector
<b>Environment</b>	Ventilation Dust & Water Proof	Fanless Front IP67
	Operating Temperature	0~60°C (32~140°F)
	Storage Temperature	-20~70°C (-4~176°F)
	Humidity	5% ~ 95% R/H, non-condensing
<b>Dimensions</b>	396.81 x 247.12x42 mm	
<b>Weight</b>	2.4 kg	
<b>Mounting</b>	VESA Moun, Panel Mount with Panel Mount bracket (Optional)	
<b>OS Supported</b>	Android 7.1 /9.0, Linux	

*\*Specifications subject to change without notice, not responsible for typographical errors.*



# MECHANICAL DRAWING:

*This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.*



Drawing No.: TNW1560HB-AO-05302023-V1