

OPEN FRAME LCD MONITOR

Open frame LCD Rear OSD with Rear Housing, 12.1" 4:3 LED High Brightness 1000nits, 1024x768, VGA Input, Side or Top OSD with Capacitive Touch (Finger only) and USB Controller



(Model: TOP1210XHB-TC)

FEATURES:

- * VGA Input / Optional DVI Input
- * Optional RCA Composite Video + Speaker / Optional HDMI Input
- * Optional 5-Wire Resistive / Capacitive Touch supports all Windows / Linux OS
- * 4:3 Screen LED Back-Light 1000nits
- * 4:3 LCD Panel with original resolution 1024x768



System Specifications

Panel	
Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel number	1024(H) x 768(V)
Pixel Pitch	0.24(H) x 0.24(V) mm
Display Size	12.1" viewable diagonal area
Active Area	245.76(H) x 184.32(V) mm
Color Depth	16.7M colors
Light Source	Long life, 50,000 hrs (typ)
Brightness	500, 1000 cd/m ² (typ)
Contrast Ratio	600 : 1
Viewing Angle	horizontal (typ) (L ~ R : - 80° ~ + 80°) vertical (typ) (U ~ D : - 80° ~ + 60°)
Input Signal	
Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh : 30 - 82Khz, Fv : 60 - 75Hz
Resolution	
Supported	1024 x 768@60 / 70 / 75 Hz 800 x 600@60 / 70 / 75 Hz 640 x 480@60 / 70 / 75 Hz 720 x 400@60 / 70 Hz 640 x 350@ 70 Hz
Recommended	1024 x 768@60 Hz
Control	
Front Panel	Power, Menu Select, + (Inc), - (Dec), Auto Adjust, Brightness, Contrast, H-Position, V-Position
Winsticker (OSD)	Phase, Color, Default, Volume, Language, Memory Recall
Power	
Input Voltage	AC: 90 to 260VAC, 50 / 60 Hz DC: 12V / 4A
Power Rating	
Operation	25 watt
Off	< 2 watt
Audio	2W x 1 Speaker
Operating Condition	
Temperature	-10 ~ 65
Humidity	10% ~ 90% (no condensation)
Storage Condition	
Temperature	- 30 ~ 70
Humidity	10% ~ 90% (no condensation)
Dimensions	
Physical	264 x 22.5 x 40.5 mm (W x H x D)
Weight	
N.W. / G.W.	3Kg / 4Kg
Options	
Video-In	
Touch Screen	5-wires Resistive type, USB OR RS-232 Interface
Certification	FCC, CE

Photo Gallery:



Drawings

