All-in-One ePoster Digital Kiosk Touchscreen 55" All-in-One ePoster Digital Kiosk, 4K Resolution 178 /178 wide-angle viewing, 450nits brightness, 1300:1 Contrast Ratio and Dual 10W Stereo Speakers w/ Infrared 10-Point Touch Model: VSK5500TSV4

FEATURES:

Interactive On-Demand Messaging

This display delivers on-demand interactive messaging with 10-point multi-touch capability and is the perfect e-catalog display solution for use as retail, information, and wayfinding kiosks in high-traffic areas.

All-in-one with Integrated Media Player

A powerful quad-core media player enables photo and video playback, while 16GB of onboard memory provides ample storage for files and multimedia content.

USB Multimedia Playback

Customized photos, music, and 4K video can be quickly displayed on-screen directly from a USB drive.

Access to Web Contents

Integrated with RJ45 connectivity, the display offers convenient web browsing functionality. Users can search online and watch videos directly on the display without having to connect to other computing devices.

Internal Scheduler

An efficient, user-friendly scheduling interface is available via the on-screen display (OSD). Setup features include time and date scheduling, ensuring that messaging, images, or videos run smoothly and on time.

Remote Various Display Management

Compatible with professional ProAV control systems such as Crestron, AMX, Extron, Control4, SureMDM, and Revel Digital, this ePoster allows IT personnel to manage and configure settings remotely over LAN with other display devices.

Media Player Cradle with Security Door

A convenient media player cradle can accommodate a PC or an additional mounted media player, while a lockable door keeps things secure and out of sight. The ePoster stand also features an integrated power supply, eliminating the need to find alternative outlets for add-on devices.

Dual 10W Speakers

Designed with dual integrated speakers, this display combines incredible screen performance with stereo sound for an immersive multimedia experience.

Premium Design

This standing all-in-one digital ePoster kiosk features a sleek and slim premium design utilizing a 7H tempered glass faceplate that offers scratch-proof protection to keep your ePoster looking like new year after year.

4K Resolution

With four-times the resolution of Full HD, this Ultra HD 3840x2160 display delivers a breathtaking viewing experience with immersive images that are vibrant, clear, and as large as life.

i-Tech Company LLC
EMAIL: info@itechlcd.com • WEB: www.iTechLCD.com

SPECIFICATIONS

Display

Panel Size: 55"

Type/Tech: TFT LCD (VA type, DLED Backlight) **Display Area (mm):** 1209.6 (H) * 680.4 (V)

Aspect Ratio: 9:16

Native Resolution: 2160 x 3840

Colors: 1.07B

Brightness: 450 nits (typ.) Contrast Ratio: 1300:1 (typ.) Response Time: 9 ms (typ. G to G) Viewing Angles: H = 178, V = 178 typ. Backlight Life: 30,000 Hours Typ. Surface Treatment: 7H Tempered Glass

Orientation: Portrait

Touch

Type/ Tech: IR Recognition Touch Resolution: 32768 x 32768

Touch Point: 10 Points

INPUT

HDMI: (2.0) x 3 RGB / VGA: x1 DisplayPort: $(1.2) \times 1$ Audio: x1 PC audio(3.5 mm)

RS232: x1

OUTPUT

Audio: x1 (Earphone out)

SPDIF: x1

LAN

RJ45: x1

USB

Type A: x3 (2.0)

Type B: x2 (for touch module)

SPEAKERS

10W x 2

COMPATIBILITY

RGB PC/HDMI PC: 1920x1080 @60Hz

HDMI: 2160 x 3840 @60Hz **DisplayPort:** 2160 x 3840 @60Hz **Android Version**

8.0

Multimedia

Image: JPG, BMP, PNG, Video: MP4, MOV, MKV, DAT,

MPG, MPEG, AVI, TS, WMV, RM, RMVB, Audio:

MP3, WAV, AAC

Bundle Software

Revel Digital, SureMDM

Power

Voltage: 100-240VAC +/- 10% Wide Range

Consumption: Normal 126 W, Max 149 W (max.), < 0.5W

OPERATING CONDITIONS

Temperature (° C): 0°C to 40°C

Humidity: 20% ~ 80% non-condensing

DIMENSIONS (W x H x D)

Physical (inch / mm): $30.26 \times 73.62 \times 17.72 \text{ in}/768.5 \times 1870 \times 100 \times 10$

Packaging (inch / mm): 38.19 x 80.08 x 23.98 in/970 x 2034

x 609 mm

WEIGHT

Net (lb / kg): 138.23 lbs/62.7 kg Gross (lb / kg): 164.69 lbs/74.7 kg

REGULATIONS

cTUVus, FCC, Energy Star, CE, CB, RoHS, ErP, EEI, WEEE,

BSMI

PACKAGE CONTENTS

1. Power Cord

2. Remote control with battery

3. Quick Start Guide

4. Key

*Actual content may differ from market to market

Modified Date: 06-20-2022

I/O Ports



- 1. LAN
- 2. RS-232C
- 3. Audio In
- 4. S/PDIF
- 5. PC In
- 6. Touch Out
- 7. USB 2.0

- 8. HDMI
- 9. DP In
- 10. AC In
- 11. Power Switch
- 12. AC Out
- 13. RJ45
- 14. USB x2