



13.3" INDUSTRIAL RUGGED TABLET

Intel® Core™ i5 8265U Whiskey Lake processor



1920 x 1080
IPS Wide Viewing
Angle LED Panel



Intel® Core™
i5 8265U
Whiskey Lake processor



Removable
Kickstand
Usable as
Carrying Handle



Magnesium Alloy
Housing
with All-around
Elastomeric Rubber



IP65
Waterproof
and Dustproof



Fanless
Cooling System



Removable Kickstand
Usable as Carrying Handle



Rich I/O with
Protective Covers



Rugged Handle Design



FC CE

MODEL: MTB133-i58

FEATURES:

- Intel® Core™ i58265U Whiskey Lake processor
- 13.3" 1920 x 1080 IPS wide viewing angle LED Panel
- Magnesium alloy housing with all-around elastomeric rubber
- Built-in kickstand usable as carrying handle(indefinitely adjustable)
- Cold swap Battery Pack
- IP65 waterproof and dustproof
- Optical bonding technology
- TPM 2.0

SPECIFICATIONS


Display			
Resolution	1920x1200	Size	13.3 inches
Contrast Ratio	1000:1	Panel Brightness	500 nits
View Angles	89,89,89,89	Type	Projected Capacitive Multi Touch
Bonding	Optical Bonding for Sunlight Viewability		
System Specification			
Processor	Intel Core i58265U 1.6GHz (up to 3.9GHz)	Memory	4GB (Default) 8GB (Optional) 16GB (Optional)
Storage	Storage 1: 1 x 128GB SSD Additional storage available with SDXC card slot (Default) Storage 1 up to 1x 1TB SSD (Optional) Storage 2 up to 1x 1TB SSD (Optional)	Security	Trusted Platform Module (TPM) 2.0 Kensington Lock
Operating System	Windows 10 IoT Enterprise LTSC (64 bit) (Default) Windows 11 IoT Enterprise LTSC (64 bit) (Optional)	WLAN	Support
BT	Support	WWAN	4G LTE (Optional)
GNSS	GPS/GLONASS (Optional)		
Mechanical			
Dimension	338.2 x 239.8 x 33.8 mm	Weight	2.2kg (w/ kickstand)
Cooling System	Fanless Design		
IO Ports			
USB Port	4 x USB 3.0 Type A, 1 x USB 3.0 Type C	SD Card Slot	1 x SDXC Slot
SD Card Slot	1 x Micro SIM card slot	Audio	2 x 1 watt speaker
LAN	1 x RJ4510/100/1000 Mbps LAN	Indicator	4x LED Indicator for Power, Battery, SSD, RF status
Docking Connector	1 x Docking connector		
Environment			
Operating Humidity	30% to 80% RH, noncondensing	Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (4°F to 140°F)	Shock	MILSTD810G Method 516.6 Procedure I
Vibration	MILSTD810G Method 514.6 Procedure I	IP rating	IP65
Drop	MILSTD810G Method 516.6 Procedure IV, 4 ft		

*Specifications subject to change without notice, not responsible for typographical errors.

Certification			
Certification	CE, FCC		
Security Function			
Kensington Lock	Kensington Lock Support		
Control			
Button	1 x Power, 1 x menu, 2 x volume key 3 x Programmable Function Keys		
Power			
Battery	15.4V, typ. 5900 mAh LiPolymer Battery (4S1P)	Battery Operating Time	More than 10 hours (BAPCo TabletMark v3)
Power Rating	19V DC	Adapter	100240V, 5060Hz / 19V DC
Accessories			
Accessories	Adapter and Power Cord Standard Battery Stylus Stand with Integrated Kickstand	Optional Accessories	Vehicle Charger (Optional) Battery Charger (Optional) Desk Docking (Optional) Handle (Optional)

MECHANICAL DRAWING

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.



Drawing No.: MTB133-i58-10022026-V1