

MILITARY GRADE RACKMOUNT LCD MONITOR



**Military Rack Mount, 17.3" LCD monitor, 1920x1080, LED-300nits
VGA, HDMI, and DVI PCAP Capacitive 2-points Touch
(Front On/Off Button for Touch) and USB Controller, Build-in 90~264V AC power.**

Front On/Off Button for Touch

MODEL: EMRW1730HD-PCT-OF

FEATURES

- Modularize mechanical design provides flexible product
- Optional build-in touch screen for interactive application, Add on/off switch for touch
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers
- Available with auto-brightness sensor offers application in day and night
- Optional: MIL connector / M12 connector / Plastic IP66 water resistance connector
- MIL-STD-1275D Power System
- MIL-STD-810G Method 514.6 Vibration
- MIL-STD-810G Method 516.6 Shock

OPTION MIL

- Environmental: MIL-STD-810, DO-160
- EMI/EMC: MIL-STD-461/462
- Panel construction & lighting: MIL-P-7788
- Power System – STD-1275D
- Shock – MIL-STD-810G Method 516.6
- Vibration – MIL-STD-810G Method 514.6



SPECIFICATION


Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 17.3" viewable diagonal area	
	Active Area / Pixel Pitch	597.89(H) x 336.31(V) mm / 0.3114(H) x 0.3114(V) mm	
	Native Resolution / Colors	1920(H) x 1080(V) / 16.7 M	
	Brightness / Contrast	300 cd/m ² (typ) / 1000 : 1	
	Response Time	≤ 5 ms	
	Viewing Angle (typical)	H. 170° (- 85° ~ + 85°) , V. 160° (- 80° ~ + 80°)	
	Light Source	LED backlight, Long life, 35,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F _H : 30 - 82Khz , F _V : 50 -75Hz
Audio System	2W speaker x 2		
Input Terminals	1 x VGA (15 Pin Female D-Sub), 1 x HDM I, 1 x DVI		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)		
Power	Build-in PCAP touch and 90~264V AC power		
Power Consumption	Around 10 watts		
Operating Condition	Temperature / Humidity	-30° ~ 80° (-22°F ~ 176°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	-30° ~ 80° (-22°F ~ 176°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	Please refer to Drawing	
	Carton	W x H x D = TBD	
Net Weight	Around 6.5kg		
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)	

**Specifications subject to change without notice, not responsible for typographical errors.*

Modified Date: 10-20-2023

MECHANICAL DRAWING

This is subject to change without Notice. Final Drawings will be Provided for Approval after Order.



Drawing No.: EMRW1730HD-PCT-OF-10202023-V2